





Brad Nail size Length: 15mm - 35mm Gauge: 18Ga



Compact & Lightweight

Cannot shoot into some materials.



Spike grips workpiece firmly regardless of the position of the contact top.

upside








Nail outlet port placed in the center of the contact top


allows for easy aiming for precision nail placement.



Counterweight mechanism

reduces vibration by moving a counterweight in the opposite direction of the piston.





Accessories



Туре	Length	Part No.
18Ga Brad Nail (5,000 pcs/box)	15mm (5/8'')	F-31867
	20mm (3/4")	F-31870
	25mm (1")	F-31883
	30mm (1-3/16")	F-31896
	35mm (1-3/8")	F-31915

Cordless Brad Nailer

DFN350 Capacity





wagazine Capacity
Shot q'ty on a single
battery charge
Vibration Level
Sound Pressure Level
Sound Power Level
Dimensions (L x W x I
•

	Length: 15 - 35 mm (5/8" - 1-3/8")
	Gauge: 18 Ga
	110
ull	w/BL1850B: 4,000
	2.5 m/s ² or less
	81 dB(A)
	92 dB(A)
)	w/BL1815N/BL1820B:
	240x79x228 mm (9-1/2"x3-1/8"x9")
	w/BL1830B/BL1840B/BL1850B/BL1860B
	257x79x228 mm (10-1/8"x3-1/8"x9")

Net weight Standard Equipment: Safety Goggles, Nose Adapter, Hex Wrench, Belt Clip, Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.

Items of standard equipment and specifications may vary by country or area.

Makita Corporation

2.1 - 2.4 kg (4.6 - 5.3 lbs.)