
#### **Cartridge type**

#### 300ml size Holder

#### Holder A Set Part No. 196351-8

- Holder A (Cartridge type)
- Holder joint A
- Rack 42
- Piston A





Cartridge type[ Piston A ]

### Cartridge type / Sausage type / **Bulk sealant type**


#### **600ml size Holder**

# Holder B Set Part No. 196352-6

- Holder B Holder joint B Rubber ring
- Nozzle Rack 64 Piston A (Cartridge type )
- Piston B (Sausage type)
- Piston C (Bulk sealant type)







Bulk sealant type Sausage type [Piston B] [ Piston C ]

# Cartridge type / Sausage type

#### 800ml size Holder

# Holder C Set Part No. 197195-9

- Holder C Holder joint C
- Holder joint C Complete
- Piston D (Cartridge type)
- Rack 53





Sausage type [ Use with Piston E ] (Part No. 143222-0)

# Li-ion Battery, Charging Time Chart (approx): min. \*with Battery fuel gauge

CXT.	<b>BL1016</b> 1.5Ah	*BL1021B 2.0Ah	*BL1041B 4.0Ah	LXT.	BL1815N 1.5Ah	*BL1820B 2.0Ah	*BL1830B 3.0Ah	*BL1840B 4.0Ah	*BL1850B 5.0Ah	*BL1860B 6.0Ah
DC10SB  DC18RE  CXT & LXT Dual port Fast Charger	22 min	30 min	<b>60</b> min	DC18RC DC18RE CXT & LXT Dual port Fast Charger	15 min	<b>24</b> min	22 min	<b>36</b> min	45 min	55 min
DC10WD	<b>50</b> min	<b>70</b> min	130 min	DC18SD	<b>30</b> min	45 min	<b>60</b> min	<b>90</b> min	110 min	130 min

# **Cordless Caulking Gun**

Variable Speed
Built-in Job Light
Carrying Case

Max pushing force No load speed

Net weight

CG100D / DCG180 CG100D 5.000 N (1.100 lbs) 0-28 mm/sec. (0-66 in/min., with Holder A set, BL1021B: 404x108x259 mm (15-7/8"x4-1/4"x10-1/4") with Holder B set, BL1021B: 538x108x259 mm (21-1/4"x4-1/4"x10-1/4") 358x108x259 rilin (21-1/4 x4-1/4 x10-1/4 ) with Holder C set, BL1021B: 480x108x267mm (18-7/8"x4-1/4"x10-1/2") with Holder A set: 1.9 - 2.1kg (4.2 - 4.5 lbs) with Holder B set: 2.5 - 2.6kg (5.5 - 5.8 lbs)

with Holder C set: 2.3 - 2.4kg (5.0 - 5.4 lbs)

DCG180 5,000 N (1,100 lbs) with Holder A set, BL1830B: 404x108x281 mm (15-7/8"x4-1/4"x11-1/8") with Holder B set, BL1830B: 538x108x281 mm (21-1/4"x4-1/4"x11-1/8") with Holder C set, BL1830B: 480x108x289 mm (18-7/8"x4-1/4"x11-3/8") with Holder A set: 2.1 - 2.4kg (4.7 - 5.4 lbs) with Holder B set: 2.6 - 3.0kg (5.8 - 6.6 lbs)

Standard Equipment: Charger, Battery, Holder, Holder Joint, Piston, Rubber Ring, Nozzle

The weight may differ depending on the attachment(s), including the battery cartridge

with Holder C set: 2.5 - 2.8kg (5.4 - 6.2 lbs)

# Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 201710







# Delivers an industry-leading 5,000 N (1,100 lbs) of dispensing force to work with the highest viscosity adhesives and sealants



## Variable speed control by dial and trigger switch

#### **Speed control dial**

enables to set maximum pushing speed for optimum sealant flow rate



#### Variable speed trigger switch

allows user to match speed to the application



#### 360 degree rotating sealant holder


Easy to work in any angle by simply rotating sealant holder



#### **Overload warning lamp**

LED light notifies when the tool is overloaded for preventing breakage of the sealant cartridge as follows:

- Blinking/The tool is nearly overloaded.
- Solid/The tool is overloaded; the overload circuit will shut off the power.



#### **LED** job light

with pre-glow and afterglow functions



#### **Anti-drip function**

relieves pressure when switch trigger is released to prevent unintentional dispensing.

# **Rubberized soft grip**

provides comfortable grip and better control.



# **■** Standard equipment

#### **Cartridge type**





window frame.



finishing

# Option Accessories

#### Cartridge type / Sausage type / Bulk sealant type



# **Holder B Set**

Part No. 196352-6



[Piston A]

Sausage type [ Piston B ]

[ Piston C ]



For Sealing work with two-component system



For Tile bonding

#### **Cartridge type / Sausage type**

800ml size Holder

# **Holder C Set**

Part No. 197195-9



[Use with Piston E] (Part No. 143222-0)





For continuous work with a thick Cartridge/ Sausage sealant