

Cordless Portable Band Saw DPB182







Stable cutting with highly rigid aluminum structure



Frame improves rigidity and prevents blade from coming

Prevents blade slipping on wheel by raising tension force.

Hook (option) for hanging on the guard rail of suspended or supported scaffolds











Wheel cover set

(option)



Easy blade replacement

by quick blade tension lever



Adjustable stopper plate convenient to cut pipes near wall, floor and ceiling.



Easy blade track adjustment simply by turning the screw

Work amount

(on a single full battery charge, battery: BL1850B)

Carbon steel pipe 48.6mm t=3.7mm

35 pcs.

M12 Thread rod

250 pcs.

Accessories

Bi-Metal Band saw blade

(5pcs./ set) Wave teeth Width: 13 mm Thickness: 0.5 mm Length: 835 mm



No. of teeth inch	Thickness of work piece	Application	Part No.
14	3-6mm	2-3mm non-ferrous metal. Mild steel, cast steel and	B-40543
18	2-3mm		B-40559
24	Less than 2mm		B-40565

Wheel cover set

Part No. 197975-3









Cordless Portable Band Saw

DPB182

Capacity	Round: 64 mm (2-1/2")
	Square pipe: 64x64 mm (2-1/2"x2-1/2")
Blade speed	3.2 m/s (630 ft/min.)
Blade Size	Length: 835 mm (32-7/8")
	Width: 13 mm (1/2")
	Thickness: 0.5 mm (0.02")
Max Output	350 W
Vibration Level	Cutting Metal: 2.5 m/s² or less
Sound Pressure Level	79 dB(A)
Dimensions (L x W x H)	477x197x229 mm (18-3/4"x7-3/4"x9")
Net weight	3.8 - 4.1 kg (8.3 - 9.0 lbs.)



Standard Equipment:

Band Saw Blade, Wheel Cover Set (Country-specific), Hook Set (Country-specific), Hex Wrench, Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.

Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan